



H-30202



H-30204.4F, H-30206.4F



H-30208.4F



H-4924



H-4930

Hornos de Mufla

Controlador	Temp. Máxima °F (°C)	Dimensiones de las Cámaras y O.D. (HxWxD)	Eléctrico	Peso Embarque lbs. (kg)	Modelo
Digital	1904 (1040)	5x4-1/4x6" (127x108x152mm); 10x14-1/2x11" O.D. (254x366x279mm O.D.)	120V, 12.5 amps, 1,500 watts, 50/60 Hz	26 (11.7)	H-30200
			230V, 6.3 amps, 1,500 watts, 50/60 Hz		H-30200.4F
	2192 (1200)	5x6-1/2x10" (127x165x254mm); 19x13-1/4x27" O.D. (482x336x685mm O.D.)	120V, 15 amps, 1,800 watts, 50/60 Hz	60 (27.2)	H-30201
			240V, 7.5 amps, 1,800 watts, 50/60 Hz		H-30201.4F
Automático de Acción Fija Simple*	1904 (1040)	5x5-1/2x13" (127x139x330mm); 26-1/2x15-1/2x24" (673x381x610mm)	120V, 35 amps, 4,100 watts, 50/60 Hz	197 (89.4)	H-30202
			240V, 17.5 amps, 4,100 watts, 50/60 Hz		H-30202.4F
Digital	1904 (1040)	12.75x10x6.8" (325x254x172mm) 12.1x29.5x21" O.D. (485x749x533mm O.D.)	230V, 10.0 amps, 2,400 watts, 50/60 Hz	110 (50)	H-30204.4F
Automático de Acción Fija Simple			230V, 18.3 amps, 4,400 watts, 50/60 Hz		H-30206.4F
Automático de Acción Fija Simple	1999 (1093)	14x14x14" (355x355x355mm) 25.5x21.5x29.5" O.D. (647x546x749mm O.D.)	230V, 22.9 amps, 5,500 watts, 50/60 Hz	110 (50)	H-30208.4F

*también están disponibles en 8 rampa, 8 intervalos programables, y puerto de comunicaciones RS232. Llame a Humboldt para mayores detalles.

Platos de Evaporación de Níquel

Descripción	Cap.	Dia. Superior in. (mm)	Altura in. (mm)	Modelo
Platos pesados de níquel puro, tienen lados rectos, fondo plano, borde de derrame.	40ml	2-1/4 (57)	1 (25)	H-4924.040
	100ml	2-3/4 (70)	1-3/8 (35)	H-4924.100
	200ml	3-3/8 (86)	1-13/16 (46)	H-4924.200
	300ml	3-7/8 (98)	2-1/4 (57)	H-4924.300

Platos de Evaporación de Porcelana

Descripción	Cap.	Dia. Superior mm	Altura mm	Modelo
Plato de porcelana poco profundo con borde de derrame, exterior enlozado parcialmente.	120ml	90	37	H-4930.120
	250ml	115	45	H-4930.250
	765ml	185	54	H-4930.765
	1285ml	215	63	H-4930.M1285