H-4929



www.humboldtdemexico.com

ventas@humboldtdemexico.com

Aluminium Moisture Boxes

Flat-bottom, straight-side seamless aluminium box has tight fitting cover, which fits bottom of box as well. Protects sample from exposure during storage and weighing operations.

Aluminium Moisture Boxes

OD	ID	Height	Inside Ht.	Volume cu. in.	Volume fl. oz.	Model
2" (51mm)	1.975 (50mm)	.875" (22mm)	0.865" (22mm)	2.650 (44cc)	1.47 (44ml)	H-4926
2.5" (64mm)	2.470 (63mm)	1.75" (44mm)	1.746" (44mm)	8.366 (137cc)	4.64 (137ml)	H-4927
3" (76mm)	3.000 (76mm)	1" (25mm)	0.985" (25mm)	6.963 (114cc)	3.86 (114ml)	H-4928
3.5" (89mm)	3.490 (89mm)	2" (51mm)	1.990" (51mm)	19.037 (312cc)	10.55 (312ml)	H-4929

Tin Sample Cups

Flat-bottom, seamless tin sample cups have telescoping covers. Hold samples for determining penetrations. Select

Tin Sample Cups

Dimensions	Set Quantity	Model
1.87" (47.7mm) ID, 1.41" (36mm) deep	48	H-1350.3A
2.42" (61.5mm) ID, 1.67" (42.6mm) deep	36	H-1350.4A
2.59" (66mm) ID, 1.72" (43.4mm) deep	36	H-1350.6A
3.05" (77.5mm) ID, 1.97" (50mm) deep	18	H-1350.8A
4" (102mm) ID, 2.375" (60.3mm) deep	1	H-1350.16
6.12" (155mm) ID, 3" (76.2mm) deep	1	H-1350.42
6.12" (155mm) ID, 5" (127mm) deep	1	H-1350.70
	1.87" (47.7mm) ID, 1.41" (36mm) deep 2.42" (61.5mm) ID, 1.67" (42.6mm) deep 2.59" (66mm) ID, 1.72" (43.4mm) deep 3.05" (77.5mm) ID, 1.97" (50mm) deep 4" (102mm) ID, 2.375" (60.3mm) deep 6.12" (155mm) ID, 3" (76.2mm) deep	1.87" (47.7mm) ID, 1.41" (36mm) deep 48 2.42" (61.5mm) ID, 1.67" (42.6mm) deep 36 2.59" (66mm) ID, 1.72" (43.4mm) deep 36 3.05" (77.5mm) ID, 1.97" (50mm) deep 18 4" (102mm) ID, 2.375" (60.3mm) deep 1 6.12" (155mm) ID, 3" (76.2mm) deep 1



Plastic transfer dish has flat bottom, straight sides and metal centering lugs with magnet in the bottom. Size is: 3-3/4" dia. x 3-1/4" deep. Meets ASTM D5.

8oz. Bacon Bomb Sampler, Brass— H-2405B 8oz. Bacon Bomb Sampler, Stainless Steel— H-2405S

Obtains samples from storage tanks, tank cars and drums using thief method. Plunger opens to admit the sample when bomb is lowered to the bottom or when plunger is released at any desired level. Plunger seals tight when bomb is withdrawn; features o-ring-type valve seal. Available in plated brass or stainless steel. Capacity: 8 oz; 2" dia. x 10" L. Meets ASTM D117, D270, D923, D943. Shipping wt. 5 lbs. (2.3kg)

16oz. Bacon Bomb Sampler, Brass— H-2407B 16oz. Bacon Bomb Sampler, Stainless Steel— H-2407S

Larger capacity with same features as H-2405. 2-3/4" dia. x 12"L. Shipping wt. 9 lbs. (4.1kg)

32oz. Bacon Bomb Sampler, Brass— H-2406B 32oz. Bacon Bomb Sampler, Stainless Steel— H-2406S

Larger capacity with same features as H-2405. 2-3/4" dia. \times 15-1/4"L. Shipping wt. 15 lbs. (6.8kg)

ASTM Oil Sampler, 3/4" Neck Opening— H-2400 ASTM Oil Sampler, 1-1/2" Neck Opening— H-2401

Weighted beaker ASTM oil sampler collects crude petroleum, petroleum products, butane, propane and other petroleum products that are gases at atmospheric temperature and pressure. Copper construction with lead-weighted bottom and bail handle. Chained cork stopper seals tight. Brass disc and loop on top allow easy removal. Corrosion-resistant paint finish. 3/4" neck opening; body is 3-3/8" dia. x 14"L. Meets ASTM D270. Shipping wt. 6 lbs. (2.7kg)





H-1352

