



H-2435.25



H-2435.20



H-2435.10



H-2435.5

25ml Cap Trap For Volatile Distillates— H-2435.25

25ml cap trap graduated 0.1ml from 0 to 25ml. Meets ASTM D95, D1461.

20ml Distillation Trap— H-2435.20

20ml distillation trap graduated in 0.2ml. Optional for ASTM D95

10ml Cap Trap For Moisture Distillates— H-2435.10

10ml cap trap graduated 0.1ml from 0 to 1ml, 0.2ml from 1ml to 10ml. Meets ASTM D95, D1461.

5ml Cap Distillation Trap— H-2435.5

5ml cap distillation trap, graduated 0.1ml. Meets ASTM D95, D1461.

Particle Charge Meter— H-2450

Particle charge meter identifies cationic emulsified asphalt, using 0-10DC millimeter controlled by variable resistor. Fail-safe design prevents exceeding meter capacity. Includes positive- and negative-identified test clips and 3-wire plug. Order stainless steel plates separately. Meets ASTM D244; AASHTO T59.



H-2450

Note: Order H-1042 Transformer for 220V operation.

Particle Charge Meter Plates— H-2452

Set of two 1" x 4" (25.4 x 101.6mm) stainless steel plates for use with H-2450.

Bitumen Soluble in Organic Solvents Set— H-1550

Used to determine solubility of asphalt cement materials. Meets ASTM D4, D2042 AASHTO T44. Shipping wt. 9 lbs.

Replacement Parts, Model H-1550

Description	Model
Gooch crucible	H-1550.1
Crucible holder	H-1550.2
Buchner funnel	H-1550.3
Glass fiber filters	H-1550.8
Chapman filter pump	H-12020
3/8" Threaded coupling	H-12155
Flask filter ring	H-4913.500
Stopper #7	H-1550.5



H-1550