Cylinder Molds

Concrete

7330313.7331008.7332358 Fax: 01

Teléfonos: 01 (

ventas@humboldtdemexico.com





Metal Cylinder Molds

Molds are constructed of plated steel for rust resistance and are dimensionally stable under severe use. Molds are split along one side with 2 guick-acting clamps welded to mold. When open, mold springs apart slightly to allow specimen removal. Include detachable base plate. Meet ASTM C31, C39, C192, C470; and AASHTO T22, T23, T126, T198.

- 6" x 12" (152 x 305mm): 1/8" (3mm) wall thickness, 1/4" (6mm) base plate. Shipping wt. 18 lbs. (8.2kg)
- 6" x 12" (152 x 305mm): Similar to above, except 1/4" (6mm) wall thickness. Shipping wt. 31 lbs (14kg)
- H-2950H— 6" x 12" (152 x 305mm): Similar to H-2950 with built-in carrying handle. Shipping wt. 32 lbs (15kg).
- 4" x 8" (102 x 203mm): 1/4" (6mm) wall thickness and base plate. Shipping wt. 8 lbs (3.6kg)
- 4" x 8" (102 x 203mm): 1/8" (6mm) wall thickness and 1/4" (6mm) base plate. Shipping wt. 8 lbs (3.6kg)
- 3" x 6" (76 x 152mm): 1/4" (6mm) wall thickness and base plate. Shipping wt. 7 lbs (3.2kg)
- 2" x 4" (51 x 102mm): 3-Gang, split, cast bronze mold has heavy rib reinforcement at top, bottom and sides. Fitted with heavy, quick-acting yoke clamps, bolts and thumbscrews for locking halves. Meets ASTM C31, C39, C192. Shipping wt. 5 lbs (2kg)

Plastic, Single-Use Cylinder Molds

Disposable plastic cylinder molds with flat plastic bottoms. Easily stripped with stripper tools (order separately). Meet ASTM C31, C39, C192, C470, C496; AASHTO T22, T23, T126, T198, M205.

- H-3041— 6" x 12" (152 x 305mm). Reinforcing rib around top opening. Lids not included. Sold in cartons of 36, oversize shipping charges apply.
- H-3041L— 6" Lid. Domed, 6" plastic lid for use with H-3041 mold. Protects specimens from damage. Sold individually.
- H-3037PML— 4" x 8" (102 x 203mm). Complete with integral, domed plastic lid. Sold in cartons of 36, oversize shipping charges apply.
- H-3038PML— 3" x 6" (76 x 152mm). Complete with integral, domed plastic lid. Sold in cartons of 80, oversize shipping charges apply.
- H-3039P— 2" x 4" (51 x 102mm). Complete with integral domed plastic lid. Sold in cartons of 84.

Plastic, Reusable Cylinder Molds

Lightweight, impact resistant construction. Will not crack, rust or deform. Can be reused up to 100 times. Meets ASTM specifications. 1/4" (6.2mm) wall thickness. Sold individually.

H-3043.6— 6" x 12" (152 x 305mm).

H-3043.4— 4" x 8" (102 x 203mm).

Cardboard Cylinder Molds

Waxed cardboard molds with flat metal bottoms. Meet ASTM C31, C39, C192, C470 C496; and AASHTO T22, T23, T126, T198.

H-3040— 6" x 12" (152 x 305mm). Carton of 24, oversize shipping charges apply

- H-3037— 4" x 8" (102 x 203mm). Carton of 50, oversize shipping charges apply.
- H-3038— 3" x 6" (76 x 152mm). Carton of 50, oversize shipping charges apply.

H-3039— 2" x 4" (51 x 1023mm). Carton of 50.

Mold Strippers

H-30415— T-Handle-style mold stripper, splits single-use cylinder molds for cylinder removal.

H-3041SMA— Screwdriver-style mold stripper, splits single-use cylinder molds cylinder removal.